

SPECIFICATIONS	10 SERIES			20 SERIES		DOUBLE	
	1040	1042	1044	2042	2044	2044D	
VOLTAGE	240			240		480	
PHASE	SINGLE			SINGLE		3PH	
AMPERAGE	FULL LOAD	50	66	66	128	128	128
	SUPPLY CIRCUIT		100	100	200	200	200
AVERAGE OUTPUT CAPACITY	LBS. PER HOUR	100	150	150	300	300	600
	LBS. PER 24 HRS.	2,400	3,600	3,600	7,200	7,200	14,400
GRAIN OUTLET HEIGHT - INCLINE 25°	45"	58"	58"	100"	100"	100"	
OVERALL DIMENSIONS	LENGTH	12'	13.5'	13.5'	23'	23'	23'
	WIDTH	3.8'	3.8'	3.8'	5.5'	5.5'	7'
	HEIGHT	63"	70"	74"	117"	117"	117"
SHIPPED WEIGHT	1,100 LBS.			1,700 LBS.		2,500 LBS.	
INSTALLED 250R GRAIN OUTLET HEIGHT	39"	47"	47"	n/a	n/a	n/a	
INSTALLED 600R GRAIN OUTLET HEIGHT	28"	37"	37"	81"	81"	72"	
CONTROL PANEL	STD.	BASIC	ADV.	BASIC	ADV.	ADV.	
PLC CONTROL			☑		☑	☑	
UL/CUL508-A		☑	☑	☑	☑	☑	
WALL MOUNTED CONTROL		☑	☑	☑	☑	☑	
MACHINE MOUNTED CONTROL	☑						
EMPTY SUPPLY PROTECTION	☑	☑	☑	☑	☑	☑	
AUGER OVERLOAD PROTECTION	☑	☑	☑	☑	☑	☑	
AUTO OVERHEAT PROTECTION	☑	☑	☑	☑	☑	☑	
HOPPER CAPACITY	3 BU.	3 BU.	3 BU.	3 BU.	3 BU.	5 BU.	

NOTE:

Dimensions will vary slightly depending on options.
Exact dimensional drawings are available by request.